

DB-624

- Specifically designed for the analysis of volatile priority pollutants and residual solvents
- No cryogenics needed for US EPA Method 502.2
- Excellent for US EPA Methods: 501.3, 502.2, 503.1, 524.2, 601, 602, 8010, 8015, 8020, 8240, 8260, and USP 467
- Excellent inertness for active compounds
- Bonded and cross-linked
- Solvent rinsable
- Exact replacement of HP-624
- Equivalent to USP Phase G43

Similar Phases: AT-624, Rxi-624 Sil MS, Rtx-624, PE-624, 007-624, 007-502, ZB-624

DB-624

| ID (mm) | Length (m) | Film (µm) | Temp Limits (°C) | 7 in Cage | 5 in Cage | 7890/6890 LTM II Module |
|-------------|------------|-------------|-------------------|-----------------|------------------|----------------------------|
| <i>0.18</i> | <i>20</i> | <i>1.00</i> | <i>-20 to 260</i> | <i>121-1324</i> | <i>121-1324E</i> | <i>121-1324LTM</i> |
| 0.20 | 25 | 1.12 | -20 to 260 | 128-1324 | 128-1324E | 128-1324LTM |
| 0.25 | 30 | 1.40 | -20 to 260 | 122-1334 | 122-1334E | 122-1334LTM |
| | 60 | 1.40 | -20 to 260 | 122-1364 | 122-1364E | |
| 0.32 | 30 | 1.80 | -20 to 260 | 123-1334 | 123-1334E | 123-1334LTM |
| | 60 | 1.80 | -20 to 260 | 123-1364 | 123-1364E | |
| 0.45 | 30 | 2.55 | -20 to 260 | 124-1334 | | 124-1334LTM |
| | 75 | 2.55 | -20 to 260 | 124-1374 | | |
| 0.53 | 15 | 3.00 | -20 to 260 | 125-1314 | | |
| | 30 | 3.00 | -20 to 260 | 125-1334 | 125-1334E | 125-1334LTM |
| | 60 | 3.00 | -20 to 260 | 125-1364 | 125-1364E | |
| | 75 | 3.00 | -20 to 260 | 125-1374 | 125-1374E | |

Agilent J&W High Efficiency GC columns are displayed using italicized descriptions and part numbers